



Porcelain Housed Surge Arrester Photo Reference



Porcelain Housed Metal Oxide Surge Arrester with Gaps

Nominal Discharge Current: 5kA

Model	MOA Rated Voltage	Power Frequency Discharge Voltage	1.2/50 μ s Impulse Discharge Voltage	8/20 μ s Lightning Current Impulse	2000 μ s Rectangular Current Impulse Withstand	4/10 μ s High Current Impulse Withstand
	kV,(rms)	kV,(rms)	\leq kV, crest	\leq kV, crest	A	kV, crest
Y5C---3	3	5.5	9	9	150	65
Y5C---6	6	11	18	18	150	65
Y5C---9	9	16	27	27	150	65
Y5C-10	10	18	30	30	150	65
Y5C-11	11	20	33	33	150	65
Y5C-12	12	22	36	36	150	65
Y5C-15	15	26	45	45	150	65
Y5C-18	18	33	54	54	150	65
Y5C-21	21	36	63	63	150	65
Y5C-24	24	40	72	72	150	65

Shed numbers and terminals can be changed to meet specific requirements.

OEM and custom size of porcelain-housed surge arresters are available upon request.



Porcelain Housed Surge Arrester Photo Reference



Porcelain Housed Metal Oxide Surge Arrester with Gaps

Nominal Discharge Current: 5kA; 10kA

Model	MOA Rated Voltage	Power Frequency Discharge Voltage	1.2/50 μ s Impulse Discharge Voltage	8/20 μ s Lightning Current Impulse	2000 μ s Rectangular Current Impulse Withstand	4/10 μ s High Current Impulse Withstand
	kV,(rms)	kV,(rms)	\leq kV, crest	\leq kV, crest	A	kV, crest
Y5C---11	11	20	33	33	150	65
Y5C---12	12	22	36	36	150	65
Y5C---15	15	26	45	45	150	65
Y5C---24	24	40	72	72	150	65
Y5C---33	33	54	99	99	150	65
Y5C---36	36	61	108	108	150	65
Y10C-11	11	18	30	30	200	65
Y10C-12	12	22	36	36	200	65
Y10C-15	15	26	45	45	200	65
Y10C-24	24	40	72	72	200	65
Y10C-33	33	56	99	99	200	65
Y10C-36	36	61	108	108	200	65

Shed numbers and terminals can be changed to meet specific requirements.

OEM and custom size of porcelain-housed surge arresters are available upon request.



Porcelain Housed Surge Arrester Photo Reference



Porcelain Housed Metal Oxide Surge Arrester with Gaps

Nominal Discharge Current: 10kA

Model	MOA Rated Voltage	Power Frequency Discharge Voltage	1.2/50 μ s Impulse Discharge Voltage	8/20 μ s Lightning Current Impulse	2000 μ s Rectangular Current Impulse Withstand	4/10 μ s High Current Impulse Withstand
	kV,(rms)	kV,(rms)	\leq kV, crest	\leq kV, crest	A	kV, crest
Y5C---3	3	5.5	9	9	200	65
Y5C---6	6	11	18	18	200	65
Y5C---9	9	16	27	27	200	65
Y5C-10	10	18	30	30	200	65
Y5C-11	11	20	33	33	200	65
Y5C-12	12	22	36	36	200	65
Y5C-15	15	26	45	45	200	65
Y5C-18	18	33	54	54	200	65
Y5C-21	21	36	63	63	200	65
Y5C-24	24	40	72	72	200	65

Shed numbers and terminals can be changed to meet specific requirements.

OEM and custom size of porcelain-housed surge arresters are available upon request.